

Bridgemark A component

prepared in accordance with Commission Regulation (EU) 2020/878 of 18 June 2020, amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

1 SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Bridgemark A component

UFI: F050-90TY-E00R-6TUA

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Professional and industrial reactive resin component for Bridgemark MMA coating and surfacing systems.

Uses advised against: Do not use for consumer applications or outside the Bridgemark MMA system.

1.3 Details of the supplier of the safety data sheet

Eurostep Poland Sp. z o.o.

95-054 Ksawerów

ul. Tymiankowa 37/39; Poland

Tel.: +48 609 222 050

Eurostep.pl

Product technical information: info@eurostep.pl

1.4 Emergency telephone number

National emergency telephone number **(Mon-Fri 8:00 – 16:00): (+48) (42) 235-28-88**

112 (emergency telephone number)

Emergency telephone number				
Country	Official advisory body	Address	Emergency number	Remark
Austria	Vergiftungsinformationszentrale (Poisons Information Centre)	Stubenring 6 1010 Wien	+43 1 406 43 43	
Belgium	Centre Anti-Poisons/ Antigifcentrum c/o Hôpital Central de la Base – Reine Astrid	Rue Bruyn 1 B -1120 Bruxelles/Brussel	+32 70 245 245	Please dial: 070 245245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)
Bulgaria	Национален токсикологичен информационен център (National Toxicological Information Centre) Многопрофилна болница за активно лечение и спешна медицина "Н.И.Пирогов" (National Clinical Toxicology Centre), Emergency Medical Institute "Pirogov"	21 Tottleben Boulevard 1606 SOFIA	+359 2 9154 409	
Croatia	Centar za kontrolu otrovanja Institut za medicinska istraživanja i medicinu rada	Ksaverska Cesta 2 p.p. 291 10000 Zagreb	+385 1 234 8342	
Cyprus	Κέντρο Δηλητηριάσεων		1401	Operating hours 24 hours / 24 hours, 7 days a week
Czech Republic	Toxikologické informační středisko Klinická pracoviště lékařství VFN a 1. LF UK	Na Bojišti 1 120 00 Praha 2	+420 224 919 293 +420 224 915 402	
Denmark	Giftlinjen Bispebjerg Hospital	Bispebjerg Bakke 23 2400 København NV	+45 82 12 12 12	
Estonia	Mürgistusteabekeskus	Gonsiori 29 15027 Tallinn	16662 +372 626 93 90	
Finland	Myrkytystietokeskus	Stenbäckinkatu 9 PO BOX 100 29 Helsinki	+358 9 471 977 +358 9 4711	
France	Centre Antipoison et de Toxicovigilance de Paris Hôpital Fernand Widal	200 rue du Faubourg Saint-Denis 75475 Paris Cedex 10	+33 1 40 05 48 48	
France	Centre Antipoison et de Toxicovigilance de Marseille Hôpital Sainte Marguerite	270 boulevard de Sainte Marguerite 13274 Marseille Cedex 09	+33 4 91 75 25 25	
Germany	Giftnotruf München Toxikologische Abteilung der II. Med. Klinik und Poliklinik rechts der Isar der Technischen Universität München	Ismaninger Straße 22 81675 München	+49 (0) 89 19240	
Germany	Giftnotruf der Charité CBF, Haus VIII (Wirtschaftsgebäude), UG	Hindenburgdamm 30 12203 Berlin	+49 (0) 30 19240	
Greece	Poisons Information Centre Children's Hospital P&A Kyriakou	11762 Athens	+30 2 10 779 3777	

Bridgemark A component

prepared in accordance with Commission Regulation (EU) 2020/878 of 18 June 2020, amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Hungary	Országos Kémiai Biztonsági Intézet Egészségügyi Toxikológiai Tájékoztató Szolgálat	Nagyvárad tér 2. 1437 Budapest, Pf. 839 1097 Budapest	+36 80 20 11 99	
Iceland	Eitrunarmiðstöð Landspítali	Fossvogi 108 Reykjavík	+354 543 22 22	
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Italy	Centro Antiveneni Dipartimento di Tossicologia Clinica, Università Cattolica del Sacro Cuore	Largo Agostino Gemelli 8 168 Roma	+39 06 305 4343	
Latvia	Valsts Toksikoloģijas centrs, Saindēšanās un zāļu informācijas centrs	Hipokrāta 2 1038 Rīga	+371 67 04 24 73	
Lithuania	Apsinuodijimų informacijos biuras	Birutės g. 56 8110 Vilnius	+370 5 236 20 52 +370 687 53378	
Luxembourg	Centre Anti-Poisons/ Antigifcentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 1120 Bruxelles/Brussel	+352 8002 5500	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital MSD Msida	+356 2545 6504	
Netherlands	Nationaal Vergiftigingen Informatie Centrum Universitair Medisch Centrum Utrecht, Het Nationaal Vergiftigingen Informatie Centrum (NVIC) informeert (dieren-) artsen, apothekers en andere professionele hulpverleners over de mogelijke gezondheidseffecten en behandelingsmogelijkheden bij vergiftigingen. Het NVIC is hiervoor dag en nacht bereikbaar, zowel telefonisch als via internet	Huispostnummer B.00.118 PO Box 85500 3508 GA Utrecht	+31 30 274 88 88	Only for the purpose of informing medical personnel in cases of acute intoxications
Norway	Giftinformasjonen Helsedirektoratet	P.O. Box 7000 St. Olavs Plass 130 Oslo	+47 22 591300	
Poland	National Poisons Information Centre The Nofer Institute of Occupational Medicine (Łódź)	ul. Teresy 8 P.O. BOX 199 90950 Łódź	+48 42 63 14 724	
Portugal	Centro de Informação Antivenenos Instituto Nacional de Emergência Médica	Rua Almirante Barroso, 36 1000-013 Lisboa	+351 808 250 143	
Romania	Department of Clinical Toxicology Spitalul de Urgenta Floreasca	Calea Floreasca Bucuresti	+40 21 230 8000	
Serbia	Nacionalni centar za kontrolu trovanja - VMA	Crnotravska 17 11000 Beograd	+381 11 360 84 40 (24h) +381 11 3672 187	
Slovakia	Národné toxikologické informačné centrum Univerzitná nemocnica Bratislava, pracovisko Kramáre, Klinikapracovnéholekárstva a toxikológie	Limbová 5 833 05 Bratislava	+421 2 54 77 41 66	
Slovenia	Center za kliničnotoksikologijo in farmakologijo Intermaklinika, UKCL	Zaloška cesta 7 1525 Ljubljana	+386 41 650 500	
Spain	Servicio de Información Toxicológica Instituto Nacional de Toxicología y Ciencias Forenses, Departamento de Sevilla	Carretera de San Jerónimo Km 0,4 41080 Sevilla	+34 91 562 04 20	(Toxicological emergencies only). Information in Spanish (24/7)
Sweden	Giftinformationscentralen	Box 60 500 171 76 Stockholm	112 – begär Giftinformation +46 10 456 6700 (Från utlandet)	(from abroad: +41 44 251 51 51) non urgent inquiry: +41 44 251 66 66
Switzerland	Tox Info Suisse	Freiestrasse 16 8032 Zürich	145	

2 SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical and chemical hazards:

Flammable liquids, Hazard Category 2 [Flam. Liq. 2]

Highly flammable liquid and vapour. (H225)

Health hazards

Skin corrosion/irritation, Hazard Category 2 [Skin Irrit. 2]

Causes skin irritation. (H315)

Bridgemark A component

prepared in accordance with Commission Regulation (EU) 2020/878 of 18 June 2020, amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Serious eye damage/eye irritation, Hazard Category 2 [Eye Irrit. 2]

Causes serious eye irritation. (H319)

Sensitisation - Skin, hazard category 1, 1A, 1B [Skin Sens.1]

May cause an allergic skin reaction. (H317)

Specific target organ toxicity - Single exposure, Hazard Category 3, [STOT SE.3]

May cause respiratory irritation. (H335)

Environmental hazards:

Hazardous to the aquatic environment - Chronic Hazard, Category 3 [Aquatic Chronic 3]

Harmful to aquatic life with long lasting effects. (H412)

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Pictogram



GHS02

GHS07

Signal word: Danger

Substances contributing to the classification

Methyl methacrylate; 2-ethylhexyl acrylate; 2-hydroxyethyl methacrylate; Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]; Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine

Hazard statement(s)

H225 Highly flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statement(s):

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Disposal

P501 Dispose of contents/container in accordance with national regulations.

2.3 Other hazards

PBT/vPvB assessment:

The mixture does not contain any components identified as persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB) at concentrations of 0.1% or higher.

Endocrine-disrupting properties – Ecological information (Section 12):

Bridgemark A component

prepared in accordance with Commission Regulation (EU) 2020/878 of 18 June 2020, amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

The mixture does not contain any components with endocrine-disrupting properties in accordance with REACH Article 57(f), Commission Delegated Regulation (EU) 2017/2100, or Commission Regulation (EU) 2018/605, at concentrations of 0.1% or higher.

Endocrine-disrupting properties – Toxicological information (Section 11):

The mixture does not contain any components with endocrine-disrupting properties in accordance with REACH Article 57(f), Commission Delegated Regulation (EU) 2017/2100, or Commission Regulation (EU) 2018/605, at concentrations of 0.1% or higher.

3 SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substances:

Not applicable.

3.2 Mixtures:

Substance identifier	Name of the substance	Weight fraction %	Classification according to Regulation (EC) No 1272/2008		
			Signal Word Code(s)	Hazard Class and Category Code(s)	Hazard Statement Code(s)
CAS No: 80-62-6 EC No: 201-297-1 Index No: 607-035-00-6 REACH-Reg No: 01-2119452498-28-xxxx	Methyl methacrylate: [1,2]	25<x<33	GHS02 GHS07 Dgr	Flam. Liq. 2 STOT SE 3 Skin Irrit. 2 Skin Sens. 1	H225 H335 H315 H317
CAS No: 103-11-7 EC No: 203-080-7 Index No: 607-107-00-7 REACH-Reg No: 01-2119453158-37-xxxx	2-ethylhexyl acrylate [1]	20<x<25	GHS07 Wng	STOT SE 3 Skin Irrit. 2 Skin Sens. 1 Aquatic Chronic 3 Notes D	H335 H315 H317 H412
CAS No: EC No: 942-960-1 Index No: REACH-Reg No:	2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester polymer with polypropylene glycol, 4-methyl-m-phenylene diisocyanate	4<x<8	GHS07 Wng	Skin Irrit. 2 Eye Irrit. 2	H319 H315
CAS No: 14807-96-6 EC No: 232-373-2 Index No: REACH-Reg No: Exempted under REACH Annex V, point 7.	Talcum [1]	3<x<6	—	Not Classified	—
CAS No: 868-77-9 EC No: 212-782-2 Index No: 607-124-00-X REACH-Reg No: 01-2119490169-29-xxxx	2-hydroxyethyl methacrylate	1<x<3	GHS07 Wng	Eye Irrit. 2 Skin Irrit. 2 Skin Sens. 1	H319 H315 H317
CAS No 7631-86-9 EC No: 231-545-4 Index No: REACH No: 01-211937949E机16-xxxx	Silicon dioxide [1]	1<x<3	—	Not Classified	—
CAS No: EC No: 911-490-9 Index No: REACH No:	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-	1<x<<1.5	GHS05 GHS07 Dgr	Acute Tox. 4 Skin Irrit. 2 Skin Sens. 1 Eye Dam. 1	H302 H315 H317 H318

Bridgemark A component

prepared in accordance with Commission Regulation (EU) 2020/878 of 18 June 2020, amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

01-2119979579-10-xxxx	hydroxyethoxy)ethyl[(4-methylphenyl)amino]-			Aquatic Chronic 3	H412
CAS No: 162627-17-0 EC No: Polymer Index No: REACH No: 01-2119970640-38-xxxx	Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine	1<x<<1.5	GHS07 Wng	Skin Sens. 1A	H317
CAS No: 107-98-2 EC No: 203-539-1 Index No: 603-064-00-3 REACH-Reg No.: 01-2119457435-35-xxxx	Mono-propylene glycol methyl ether [1,2]	<1	GHS02 GHS07 Wng	Flam. Liq. 3 STOT SE 3	H226 H336
CAS No: 64742-95-6 EC No: 219-163-6 Index No: REACH No: 01-2119455851-35-xxxx	Solvent naphtha (petroleum), light arom]	<0.3	GHS07 GHS08 Dgr	Flam. Liq. 3 Asp. Tox. 1 STOT SE 3 STOT SE 3 Aquatic Chronic 2	H226 H304 H335 H336 H411 EUH066

Legend:

[1] Substance with a national occupational exposure limit (OEL). See section 8.

[2] Substance with a European Union occupational exposure limit (OEL). See section 8

Full text of H-statements is given in Section 16.

4 SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

Inhalation:

Move the affected person to fresh air and keep them in a position comfortable for breathing. Keep warm and at rest. If respiratory irritation or symptoms persist, seek medical advice.

Skin contact:

Remove contaminated clothing immediately. Wash skin thoroughly with plenty of water. If skin irritation occurs, seek medical attention.

Eye contact:

Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists, seek medical advice.

Ingestion:

Do NOT induce vomiting. Immediately call a POISON CENTRE or a doctor. If the person is conscious, rinse the mouth. Aspiration into the respiratory tract may occur.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in Section 2.2 (label elements) and/or in Section 11.

4.3 Indication of any immediate medical attention and special treatment needed

In the event of severe symptoms or if there is any doubt, medical advice should be sought immediately. The safety data sheet or product label should be provided to the physician without delay.

5 SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media:

Use extinguishing media appropriate to the surrounding fire: water spray, foam, dry powder or carbon dioxide.

Bridgemark A component

prepared in accordance with Commission Regulation (EU) 2020/878 of 18 June 2020, amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Unsuitable extinguishing media:

Jet water.

5.2 Special hazards arising from the substance or mixture

The product is flammable. Under fire conditions it presents a risk of sudden ignition and rapid flame spread. Vapours are heavier than air and may accumulate at ground level, creating areas with an increased ignition risk. Flammable mixtures with air may form in confined spaces. During a fire, toxic decomposition products may be generated, including carbon oxides and irritating aerosols.

5.3 Advice for firefighters

Personal protection typical in case of fire. Do not stay in the fire zone without self-contained breathing apparatus and protective clothing resistant to chemicals. Do not let extinguishing water to reach drainage system, surface water and groundwater. Collect used extinguishing media.

6 SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Limit access of bystanders to the accident area until proper cleaning operations are completed. In case of major leaks, isolate the affected area. Avoid direct contact with the released product. Avoid inhaling vapours or spray. Use personal protective equipment. Ensure adequate ventilation.

For emergency responders: Ensure that the response and clean-up operations is carried out only by trained personnel. Use individual protection measures.

6.2 Environmental precautions

In the event of a large release, take appropriate steps to prevent environmental spread. Prevent the product from entering the sewer system. Notify relevant emergency services.

6.3 Methods and material for containment and cleaning up

Absorb the spilled liquid with an inert material (e.g. sand, diatomaceous earth or mineral sorbent) and place it in suitable, labelled containers for disposal in accordance with local regulations. Clean the contaminated surface with water and detergent; solvents must not be used due to the risk of forming flammable vapours. Remove all ignition sources from the affected area and ensure adequate ventilation.

6.4 Reference to other sections

Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

7 SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid breathing vapours or aerosols. Use only in well-ventilated areas or with adequate local exhaust ventilation. Wear appropriate personal protective equipment. Do not eat, drink or smoke when using this product. Follow standard workplace hygiene practices; wash hands after handling.

7.2 Conditions for safe storage, including any incompatibilities

Store in tightly closed original containers in a cool, dry and well-ventilated area. Protect from direct sunlight and from sources of heat and ignition. Do not store together with strong oxidising agents, acids or bases.

7.3 Specific end use(s)

No information on applications other than those listed in subsection 1.2.

8 SECTION 8: EXPOSURE CONTROLS/ PERSONAL PROTECTION

8.1 Control parameters

Methyl methacrylate CAS-No.: 80-62-6

Bridgemark A component

prepared in accordance with Commission Regulation (EU) 2020/878 of 18 June 2020, amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Australia: TWA 50 ppm (208 mg/m³); STEL 100 ppm (416 mg/m³). Remark: 15 min average value.
Austria: TWA 50 ppm (210 mg/m³); STEL 100 ppm (420 mg/m³). Remark: Ceiling limit value (5 minutes).
Belgium: TWA 50 ppm (208 mg/m³); STEL 100 ppm (416 mg/m³). Remark: 15 min average value.
Canada – Ontario: TWA 50 ppm; STEL 100 ppm.
Canada – Québec: TWA 50 ppm; STEL 100 ppm. Remark: 15 min average value.
Denmark: TWA 25 ppm (102 mg/m³). Remark: Skin. STEL 50 ppm (204 mg/m³). Remark: 15 min average value.
European Union (IOELV): TWA 50 ppm; STEL 100 ppm. Remark: 15 min average value.
Finland: TWA 10 ppm (42 mg/m³); STEL 50 ppm (210 mg/m³). Remark: 15 min average value.
France: TWA 50 ppm (205 mg/m³); STEL 100 ppm (410 mg/m³). Remark: 15 min average value, restrictive statutory value.
Germany (AGS): TWA 50 ppm (210 mg/m³); STEL 100 ppm (420 mg/m³). Remark: 15 min average value.
Germany (DFG): TWA 50 ppm (210 mg/m³); STEL 100 ppm (420 mg/m³). Remark: 15 min average value.
Hungary: TWA 208 mg/m³ (Skin); STEL 415 mg/m³. Remark: 15 min average value.
Ireland: TWA 50 ppm; STEL 100 ppm. Remark: 15 min reference period.
Israel: TWA 50 ppm (205 mg/m³).
Italy: TWA 50 ppm; STEL 100 ppm. Remark: 15 min average value.
Japan (JSOH): TWA 8.3 mg/m³.
Latvia: TWA 10 mg/m³.
New Zealand: TWA 50 ppm (208 mg/m³). Remark: Skin. STEL 100 ppm (416 mg/m³). Remark: 15 min average value.
Norway: TWA 25 ppm (100 mg/m³); STEL 100 ppm (400 mg/m³). Remark: 15 min average value.
People's Republic of China: TWA 100 mg/m³.
Poland: TWA 100 mg/m³; STEL 300 mg/m³. Remark: 15 min average value.
Romania: TWA 50 ppm (205 mg/m³); STEL 100 ppm (410 mg/m³). Remark: 15 min average value.
Singapore: TWA 100 ppm (410 mg/m³).
South Africa: TWA 100 ppm; STEL 200 ppm. Remark: 15 min average value.
South Africa – Mining: TWA 50 ppm (205 mg/m³); STEL 100 ppm (410 mg/m³). Remark: 15 min average value.
South Korea: TWA 50 ppm; STEL 100 ppm. Remark: 15 min average value.
Spain: TWA 50 ppm (100 mg/m³); STEL 100 ppm (416 mg/m³). Remark: 15 min average value.
Sweden: TWA 50 ppm (200 mg/m³); STEL 100 ppm (400 mg/m³). Remark: 15 min average value.
Switzerland: TWA 50 ppm (210 mg/m³); STEL 100 ppm (420 mg/m³).
The Netherlands: TWA 50 ppm (205 mg/m³); STEL 100 ppm (410 mg/m³). Remark: 15 min average value.
USA – NIOSH: TWA 100 ppm (410 mg/m³).
USA – OSHA: TWA 100 ppm (410 mg/m³).
United Kingdom: TWA 50 ppm (208 mg/m³); STEL 100 ppm (416 mg/m³). Remark: 15 min average value.

General remarks:

Bold-type values in EU: Indicative Occupational Exposure Limit Values (IOELV).

Some countries specify additional notations (e.g., skin, sensitiser). Always consult national regulations.

Talc CAS No.: 14807-96-6

Australia TWA: 2.5 mg/m³

Austria TWA: 2 mg/m³ (respirable fraction)

Belgium TWA: 2 mg/m³ (respirable fraction, asbestos-free)

Canada – Ontario

TWA: 2 mg/m³ (respirable fraction, particulate matter containing no asbestos and <1% crystalline silica)

STEL: 2 mg/m³ (respirable particulate mass; should not be exceeded)

Canada – Québec

TWA: 2 mg/m³ (respirable fraction)

STEL: 1 mg/m³

Denmark

TWA: 0.3 mg/m³ (respirable fraction)

Bridgemark A component

prepared in accordance with Commission Regulation (EU) 2020/878 of 18 June 2020, amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

STEL: 0.6 mg/m³ (respirable fraction)

Finland

TWA: 1 mg/m³ (respirable fraction)

STEL (15-minute average): 1 mg/m³

TWA: 0.5 mg/m³ (inhalable fraction)

STEL (15-minute average): 2 mg/m³ (inhalable fraction)

Hungary TWA: 2 mg/m³ (respirable fraction)

Ireland

TWA: 0.8 mg/m³ (respirable fraction)

TWA: 10 mg/m³ (inhalable fraction)

Israel

TWA: 4 mg/m³ (inhalable fraction)

TWA: 2 mg/m³ (respirable fraction)

Japan (JSOH)

TWA: 1 mg/m³ (respirable fraction, asbestos- and crystalline silica-free)

TWA: 4 mg/m³ (inhalable fraction, asbestos- and crystalline silica-free)

Latvia TWA: 4 mg/m³

New Zealand TWA: 2 mg/m³ (respirable fraction, containing no asbestos)

Norway

TWA: 2 mg/m³ (respirable fraction)

TWA: 6 mg/m³ (total dust)

People's Republic of China

TWA: 1 mg/m³ (respirable fraction)

TWA: 3 mg/m³ (inhalable fraction)

Poland

TWA: 1 mg/m³ (respirable fraction)

TWA: 4 mg/m³ (inhalable fraction)

Singapore TWA: 2 mg/m³

South Africa TWA: 4 mg/m³ (respirable fraction; particulate matter containing no asbestos and ≤1% crystalline silica)

South Africa – Mining

TWA: 1 mg/m³ (respirable fraction)

TWA: 10 mg/m³ (inhalable fraction)

South Korea TWA: 2 mg/m³

Spain TWA: 2 mg/m³ (respirable aerosol)

Sweden

TWA: 1 mg/m³ (respirable aerosol)

TWA: 2 mg/m³ (inhalable aerosol)

Switzerland TWA: 3 mg/m³ (respirable fraction)

The Netherlands TWA: 0.25 mg/m³ (respirable fraction)

USA – NIOSH REL (TWA): 2 mg/m³ (respirable fraction, containing no asbestos)

USA – OSHA PEL: 20 mppcf

Note: mppcf × 35.3 = million particles per cubic meter

United Kingdom WEL (TWA): 1 mg/m³ (respirable fraction)

General remarks

The above occupational exposure limits apply to talc that is asbestos-free and crystalline silica-free, unless otherwise stated.

2-Ethylhexyl acrylate CAS No.: 103-11-7

Austria:

Limit value — TWA: 10 ppm / 82 mg/m³.

Bridgemark A component

prepared in accordance with Commission Regulation (EU) 2020/878 of 18 June 2020, amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Limit value — STEL / ceiling limit value: 10 ppm / 82 mg/m³.

Remark: Ceiling limit value.

Germany — AGS:

Limit value — TWA: 5 ppm / 38 mg/m³.

Limit value — STEL: 5 ppm / 38 mg/m³.

Remarks: Inhalable aerosol and vapour. STEL value refers to a 15-minute reference period.

Germany — DFG:

Limit value — TWA: 5 ppm / 38 mg/m³.

Limit value — STEL: 5 ppm / 38 mg/m³.

Remarks: Inhalable fraction and vapour. STEL value refers to a 15-minute average value.

Latvia:

Limit value — TWA: 1 mg/m³.

Limit value — STEL: Not established.

Poland:

Limit value — TWA: 35 mg/m³.

Limit value — STEL: 70 mg/m³.

Remarks: Skin notation. STEL value refers to a 15-minute average value.

Switzerland:

Limit value — TWA: 5 ppm / 38 mg/m³.

Limit value — STEL: 5 ppm / 38 mg/m³.

Silicon dioxide, amorphous CAS No.: 7631-86-9, 112926-00-8

Australia – 2 mg/m³ (inhalable dust containing no asbestos and <1% crystalline silica)

Austria – 4 mg/m³ (inhalable fraction)

Belgium – 10 mg/m³

Canada (Ontario) – 10 mg/m³

Canada (Québec) – 6 mg/m³ (respirable fraction; dust containing no asbestos and <1% crystalline silica)

Finland – 5 mg/m³

Germany (AGS) – 1 mg/m³ inhalable fraction; 8 mg/m³ short-term value (15 min)

Germany (DFG) – 0.02 mg/m³ respirable fraction; 0.16 mg/m³ short-term value

Ireland – 2.4 mg/m³ respirable fraction; 6 mg/m³ inhalable fraction

Latvia – 1 mg/m³

New Zealand – 10 mg/m³ (inhalable fraction)

Norway – 1.5 mg/m³ (respirable fraction)

China – 2 mg/m³ (inhalable fraction)

Poland – 2 mg/m³ respirable fraction; 10 mg/m³ inhalable fraction

Singapore – 10 mg/m³

South Africa (Mining) – 3 mg/m³ respirable fraction; 6 mg/m³ inhalable fraction

South Korea – 10 mg/m³

Switzerland – 2 mg/m³ inhalable fraction

USA (NIOSH) – 6 mg/m³

USA (OSHA) – 20 mppcf

United Kingdom – 2.4 mg/m³ respirable fraction; 6 mg/m³ inhalable fraction

1-Methoxypropan-2-ol CAS-No.: 107-98-2

European Union (IOELV): 100 ppm / 375 mg/m³ (TWA), 150 ppm / 568 mg/m³ (STEL), Skin, 15 min.

Australia: 100 ppm / 369 mg/m³ (TWA), 150 ppm / 553 mg/m³ (STEL), 15 min.

Austria: 50 ppm / 187 mg/m³ (TWA), 50 ppm / 187 mg/m³ (Ceiling), Skin.

Belgium: 50 ppm / 184 mg/m³ (TWA), 100 ppm / 369 mg/m³ (STEL), Skin, 15 min.

Canada (Ontario): 100 ppm (TWA), 150 ppm (STEL).

Canada (Québec): 100 ppm / 369 mg/m³ (TWA), 150 ppm / 553 mg/m³ (STEL), 15 min.

Bridgemark A component

prepared in accordance with Commission Regulation (EU) 2020/878 of 18 June 2020, amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Denmark: 50 ppm / 185 mg/m³ (TWA), 100 ppm / 370 mg/m³ (STEL), Skin, 15 min.
 Finland: 100 ppm / 370 mg/m³ (TWA), 150 ppm / 560 mg/m³ (STEL), 15 min.
 France: 50 ppm / 188 mg/m³ (TWA), 100 ppm / 375 mg/m³ (STEL), Skin, 15 min.
 Germany (AGS/DFG): 100 ppm / 370 mg/m³ (TWA), 200 ppm / 740 mg/m³ (STEL), 15 min.
 Hungary: 375 mg/m³ (TWA), 568 mg/m³ (STEL), Skin, 15 min.
 Ireland: 100 ppm / 375 mg/m³ (TWA), 150 ppm / 568 mg/m³ (STEL), 15 min.
 Israel: 100 ppm / 369 mg/m³ (TWA).
 Italy: 100 ppm / 375 mg/m³ (TWA), 150 ppm / 568 mg/m³ (STEL), Skin, 15 min.
 Latvia: 100 ppm / 375 mg/m³ (TWA), 150 ppm / 568 mg/m³ (STEL), 15 min.
 New Zealand: 100 ppm / 369 mg/m³ (TWA), 150 ppm / 553 mg/m³ (STEL), 15 min.
 Norway: 50 ppm / 180 mg/m³ (TWA), Skin.
 Poland: 180 mg/m³ (TWA), 360 mg/m³ (STEL), Skin.
 Romania: 100 ppm / 375 mg/m³ (TWA), 150 ppm / 568 mg/m³ (STEL), 15 min.
 South Africa: 100 ppm (TWA), 200 ppm (STEL), Skin, 15 min.
 South Africa (Mining): 100 ppm / 370 mg/m³ (TWA), 150 ppm / 550 mg/m³ (STEL), Skin, 15 min.
 South Korea: 100 ppm (TWA), 150 ppm (STEL), 15 min.
 Spain: 100 ppm / 375 mg/m³ (TWA), 150 ppm / 568 mg/m³ (STEL), Skin.
 Sweden: 50 ppm / 190 mg/m³ (TWA), 150 ppm / 568 mg/m³ (STEL), 15 min.
 Switzerland: 100 ppm / 360 mg/m³ (TWA), 200 ppm / 720 mg/m³ (STEL).
 The Netherlands: 100 ppm / 375 mg/m³ (TWA), 150 ppm / 563 mg/m³ (STEL), Skin, 15 min.
 USA (NIOSH): 100 ppm / 360 mg/m³ (TWA), 150 ppm / 540 mg/m³ (STEL), 15 min.
 United Kingdom: 100 ppm / 375 mg/m³ (TWA), 150 ppm / 560 mg/m³ (STEL), Skin, 15 min.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Use only in well-ventilated areas. Provide effective general ventilation and, during application, transfer, mixing or work with open containers, local exhaust ventilation.
 Do not breathe vapours or spray. Prevent the formation of vapour concentrations in air exceeding occupational exposure limits and flammable/explosive concentrations.
 Due to the flammable properties of the product, use electrical, ventilation and process equipment suitable for explosive atmospheres where required by the workplace risk assessment. Ground and bond containers and equipment during transfer operations. Remove ignition sources. Use non-sparking tools.
 Provide access to eyewash facilities and means for rapid skin washing.

8.2.2 Individual protection measures, such as personal protective equipment

Eye/face protection:

Wear tightly fitting safety goggles or protective glasses compliant with EN 166.

Hand protection:

Wear chemical-resistant protective gloves complying with EN ISO 374.

Recommended glove material: butyl rubber or laminated/barrier gloves suitable for organic solvent mixtures, including ketones and aromatic hydrocarbons.

Indicative working parameters:

Parameter

Material

Breakthrough time

Thickness

Standard

Recommendation

butyl rubber / laminated barrier gloves

preferably > 480 min

select according to glove manufacturer's recommendation

EN ISO 374

Skin and body protection:

Use antistatic and chemical-resistant protective clothing compliant with EN 13034 / EN 1149 to prevent skin contact.

Respiratory protection:

Bridgemark A component

prepared in accordance with Commission Regulation (EU) 2020/878 of 18 June 2020, amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

With adequate ventilation and where occupational exposure limits are not exceeded, respiratory protection is not required. In case of inadequate ventilation, work in poorly ventilated areas, exceedance of occupational exposure limits or nuisance vapour concentrations, use respiratory protective equipment with an organic vapour filter:

Working conditions

Solvent vapours

Vapours + aerosol/spray

High concentrations / confined spaces /
oxygen deficiency

Respiratory protective equipment shall be selected on the basis of workplace risk assessment and occupational exposure monitoring results.

Recommended protectionhalf-mask/full-face mask with type **A** filtercombined **A/P2** or **A/P3** filter

self-contained or supplied-air breathing apparatus

Hygiene measures:

Do not eat, drink or smoke when using the product. Wash hands before breaks and after finishing work.

8.3 Environmental exposure controls

Prevent release to drains, surface water, groundwater and soil. Protect drains. For larger quantities, provide secondary containment/bunding. Dispose of waste and contaminated packaging through an authorised waste contractor in accordance with section 13.

9 SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state:	Viscous liquid / paste.
Colour:	Not determined
Odour:	Characteristic acrylic / ester-like odour
Melting point/freezing point:	Not determined
Boiling point or initial boiling point and boiling range:	Approx. 100°C
Flammability:	Flammable
Lower and upper explosion limit:	Not determined
Flash point:	<23°C
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
pH:	Not determined
Kinematic viscosity:	Not determined
Solubility:	Water: insoluble / practically insoluble
Partition coefficient n-octanol/water (log value):	Not determined
Vapour pressure:	Not determined
Density and/or relative density:	Not determined
Relative vapour density:	Not determined
Particle characteristics:	Not applicable (liquid)

9.2 Other information**9.2.1 Information with regard to physical hazard classes**

Flammable liquids	Flam. Liq. 2; H225 — Highly flammable liquid and vapour
Explosive properties	No explosive properties known; the mixture is not classified as explosive
Oxidising properties	No oxidising properties known; the mixture is not classified as oxidising

Bridgemark A component

prepared in accordance with Commission Regulation (EU) 2020/878 of 18 June 2020, amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

9.2.2 Other safety characteristics

Volatile organic compounds, VOC content: calculated value 52.1–55.1% w/w, approx. 521–551 g/kg.

10 SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

The product contains reactive acrylate and methacrylate components. No dangerous reactivity is expected under recommended conditions of use, storage and transport. Vapours may form flammable or explosive mixtures with air.

10.2 Chemical stability

The product is chemically stable under normal conditions of use and storage.

10.3 Possibility of hazardous reactions

No hazardous reactions are known when the product is used as intended. Contact with strong oxidising agents may cause hazardous reactions.

10.4 Conditions to avoid

Avoid heat, ignition sources, sparks, open flames, direct sunlight and electrostatic discharge. Do not allow vapours to accumulate in confined or poorly ventilated areas. Avoid heat, sparks, open flames, hot surfaces, electrostatic discharge, direct sunlight and insufficient ventilation. Avoid uncontrolled evaporation or concentration of volatile monomers.

10.5 Incompatible materials

Avoid contact with strong oxidising agents, peroxides, radical initiators, strong acids, strong bases and strong reducing agents. Avoid unintended contact with the curing or initiator component.

10.6 Hazardous decomposition products

No hazardous decomposition products are expected under normal conditions of use. In case of fire, carbon monoxide, carbon dioxide and irritating or toxic fumes and vapours may be formed.

11 SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity:

ATE MIX oral (mg/kg): >2000. Based on available data, the classification criteria are not met.

ATE MIX dermal (mg/kg): >2000. Based on available data, the classification criteria are not met

ATE MIX inhalation (mg/l/4h): >20. Based on available data, the classification criteria are not met

The acute toxicity of the mixture (ATEmix) is calculated based on the appropriate conversion coefficient contained in Table 3.1.2 of Annex I to the CLP regulation, as amended.

Skin corrosion/irritation:

Causes skin irritation.

Serious eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation:

May produce an allergic reaction.

Germ cell mutagenicity:

Based on available information, classification criteria are not met.

Carcinogenicity:

Based on available information, classification criteria are not met.

Reproductive toxicity:

Based on available information, classification criteria are not met.

STOT-single exposure:

May cause respiratory irritation

Bridgemark A component

prepared in accordance with Commission Regulation (EU) 2020/878 of 18 June 2020, amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

STOT-repeated exposure:

Based on available information, classification criteria are not met.

Aspiration hazard:

Based on available information, classification criteria are not met.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

The product does not contain substances included in the list established in accordance with Article 59 (1) for having endocrine disrupting properties, or substances identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 (3) or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0.1 % by weight.

11.2.2 Other information

Not applicable to substances.

12 SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data for the mixture.

12.3 Bioaccumulative potential

No data for the mixture.

12.4 Mobility in soil

No data are available for the mixture. Based on available component data, significant bioaccumulation of the mixture as a whole is not expected. The mobility of the substances depends on their hydrophilic and hydrophobic properties and abiotic and biotic conditions of soil, including its structures, climatic conditions, seasons and soil organisms, mainly (bacteria, fungi, algae, invertebrates).

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted.

12.6 Endocrine disrupting properties

Based on available data, the mixture does not contain components with endocrine disrupting properties at concentrations requiring consideration in this section.

12.7 Other adverse effects

The product contains volatile organic solvents. Avoid release to the environment. Spills may cause local contamination of soil, drains and water.

13 SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Disposal methods for the product:

Waste product and product residues should be disposed of in accordance with applicable national and local regulations. Do not discharge into drains, surface water or soil.

Product residues should be treated as hazardous waste.

Recommended waste code: **08 01 11*** — waste paint and varnish containing organic solvents or other hazardous substances. The final waste code should be assigned by the waste holder according to the source and process generating the waste.

Disposal methods for used packing: reuse/recycle/eliminate empty containers in accordance with the local legislation. Only completely emptied packaging can be recycled.

Bridgemark A component

prepared in accordance with Commission Regulation (EU) 2020/878 of 18 June 2020, amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Contaminated packaging should be emptied as far as possible and disposed of in accordance with applicable regulations. Packaging containing product residues may be classified under waste code **15 01 10*** — packaging containing residues of or contaminated by hazardous substances.

Legal basis: Directive 2008/98/EC, 94/62/EC.

14 SECTION 14: TRANSPORT INFORMATION

The mixture is subject to regulations related to the transport of hazardous goods as outlined in ADR (road transport), RID (railway transport), ADN (inland waterway transport), IMDG (maritime transport), and ICAO/IATA (aviation transport).

14.1 UN number or ID number

ADR/RID/IMDG/IATA: **UN 1866**

14.2 UN proper shipping name

RESIN SOLUTION

14.3 Transport hazard class (es)

ADR/RID/IMDG/IATA: 3

14.4 Packing group

ADR/RID/IMDG/IATA: II

14.5 Environmental hazards

ADR/RID/IMDG/IATA: Product is not classified as dangerous for the environment in accordance with transport regulations.

14.6 Special precautions for user**ADR**

Classification code: F1
Tunnel restriction code: [D/E]
Transport category: 2
Limited Quantity: 5 L
Excepted quantities: E2
Packing instructions: P001 IBC02; R001
Mixed Packing: MP19
Special provisions 8.5: S2, S20
Hazard identification No.: 33

RID

Classification code: F1
Transport Category: 3
Limited Quantities: 5L
Excepted Quantities: E2
Mixed Packing: MP19
Packing instructions: 'P001 IBC02; R001
Express Parcels: CE7
Hazard Identification Number: 33

IMDG

EmS Code: F-E, S-E
Stowage category: B
Limited Quantities: 5L

Bridgemark A component

prepared in accordance with Commission Regulation (EU) 2020/878 of 18 June 2020, amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Excepted Quantities:	E2
Packing instructions:	P001; IBC02
IATA	
Hazard label:	Flammable liquid
<u>Passenger and Cargo Aircraft</u>	
Excepted quantities (IATA):	E2
Limited quantities (IATA):	Y341
Maximum net quantity for limited quantities (IATA):	1 L
Packing instruction (IATA):	353
Maximum net quantity per package (IATA):	5 L
<u>Cargo Aircraft Only</u>	
Packing instruction (IATA):	364
Maximum net quantity per package (IATA):	60 L
Special provisions (IATA):	A3
ERG code (IATA):	3L

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

15 SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Seveso III Directive (2012/18/EU):

The mixture is classified according to the hazard categories defined in the Seveso III Directive:

P5c – Flammable liquids (Categories 2 and 3)

Quantity thresholds according to the Seveso III Directive:

P5c – Lower-tier establishment: 5,000 t, upper-tier establishment: 50,000 t

EU legislation

- Regulation (EC) No 1907/2006** concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94, as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
- Commission Regulation (EU) 2020/878** of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.
- Regulation (EC) No 648/2004 of the European Parliament and of the Council** of 31 March 2004 on detergents.
- Regulation (EU) No 2026/405** of 11 February 2026 on detergents and surfactants and repealing Regulation (EC) No 648/2004.
- Regulation (EC) No 1013/2006 of the European Parliament and of the Council** of 14 June 2006 on shipments of waste.
- Regulation (EU) No 649/2012 of the European Parliament and of the Council** of 4 July 2012 concerning the export and import of hazardous chemicals.
- Regulation (EC) No 1223/2009 of the European Parliament and of the Council** of 30 November 2009 on cosmetic products.
- Regulation (EC) No 1272/2008** on classification, labelling and packaging of substances and mixtures (CLP), taking into account the latest adaptations to technical progress (ATP).

Bridgemark A component

prepared in accordance with Commission Regulation (EU) 2020/878 of 18 June 2020, amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

21. **Regulation (EU) 2019/1021 of the European Parliament and of the Council** of 20 June 2019 on persistent organic pollutants, recasting Regulation (EC) No 850/2004.
22. **Regulation (EU) 2019/1148 of the European Parliament and of the Council** of 20 June 2019 on the marketing and use of explosives precursors.
23. **Directive 94/62/EC of the European Parliament and of the Council** of 20 December 1994 on packaging and packaging waste, as amended.
24. **Directive 2008/98/EC of the European Parliament and of the Council** of 19 November 2008 on waste and repealing certain Directives, Text with EEA relevance, as amended.
25. **Directive 2012/19/EU of the European Parliament and of the Council** of 4 July 2012 on waste electrical and electronic equipment (WEEE Directive).

15.2 Chemical safety assessment

The supplier has not assessed chemical safety. It is not required for the mixture.

16 SECTION 16: OTHER INFORMATION

Other sources of information:

IUCLID Data Bank (European Commission – European Chemicals Bureau).

ESIS – European Chemical Substances Information System (European Chemicals Bureau).

Classification according to Regulation (EC) No 1272/2008

STOT SE 3	H335	calculation method
Skin Irrit. 2	H315	calculation method
Eye Irrit. 2	H319	calculation method
Skin sens 1	H317	calculation method
Aquatic Chronic 3	H412	calculation method
Flam. Liq. 2	H225	Flash point

H (hazard) phrases specified in point 2 and 3 hereof:

H319	Causes serious eye irritation
Eye Irrit. 2	Serious eye damage/eye irritation, Hazard Category 2.
H335	May cause respiratory irritation.
STOT SE 3	Specific target organ toxicity — Single exposure, Hazard Category 3, Respiratory tract irritation.
H225	Highly flammable liquid and vapour
Flam. Liq. 2	Flammable liquids, Hazard Category 2.
H315	Causes skin irritation
Skin Irrit. 2	Skin corrosion/irritation, Hazard Category 2
H226	Flammable liquid and vapour.
Flam. Liq. 3	Flammable liquids, Hazard Category 3.
EUH 066	Repeated exposure may cause skin dryness or cracking
H336	May cause drowsiness or dizziness.
STOT SE 3	Specific target organ toxicity -Single exposure, Hazard Category 3, Narcosis
H412	Harmful to aquatic life with long lasting effects.
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3.
H317	May cause an allergic skin reaction.

Bridgemark A component

prepared in accordance with Commission Regulation (EU) 2020/878 of 18 June 2020, amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Skin Sens. 1	Sensitisation — Skin, hazard category 1, 1A, 1B.
H302	Harmful if swallowed .
Acute Tox 4	Acute toxicity (oral), Hazard Category 4
H318	Causes serious eye damage.
Eye Dam 1	Serious eye damage/eye irritation, Hazard Category 1.

Explanation of returns

ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
DGR	Dangerous Goods Regulations (see IATA/DGR)
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EH40/2005	Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
GHS "	Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
index No	the Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
STEL	short-term exposure limit
SVHC	Substance of Very High Concern
TWA	time-weighted average
VOC	Volatile Organic Compounds
vPvB	very Persistent and very Bioaccumulative
WEL	workplace exposure limit

Bridgemark A component

prepared in accordance with Commission Regulation (EU) 2020/878 of 18 June 2020, amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Training

Prior to working with the product you should be familiar with safety rules for handling the chemicals, in particular take proper workplace training. **People associated with the transport of hazardous materials in accordance with ADR** should be adequately trained to perform their duties (general training, bench and safety).

The provided information is based on current data and the manufacturer's knowledge and experience regarding the product. The Safety Data Sheet serves as guidance for safe handling during transport, distribution, application, and storage, but it does not certify the product's quality. The information is specific to the named product and may not apply to its use with other materials or in different applications. Users are responsible for complying with all applicable standards and regulations and bear responsibility for any misuse of the information in the Safety Data Sheet or improper use of the product.