

EUROSTEP MMA FL

Flake system

Version 1.0 - November 2024

3 layer flake system applied at 2-4 mm. System is used in commercial areas, retail and public spaces. Depending on the requested aesthetic this system can either be fully broadcasted with flakes or partially.



APPLICATIONS:

- Office buildings and business centers
- Restaurants, cafés, and food courts
- Banks and financial institutions
- Hotels and conference centers
- Shopping malls and department stores
- Supermarkets and grocery stores
- Standalone retail stores and boutiques

ADVANTAGES:

- Aesthetically pleasing, various finishes possible
- Fast installation (can be applied up to -30 degrees Celsius)
- Adjustable level of antislip
- Easy to clean
- Chemical resistance
- Mechanical strength
- Seamless finish
- UV stability

SYSTEM:

1 st layer:	Primer Plex 1120:	0,4 kg/m ²
	Natural quartz 0,8-1,4:	0,6 kg/m ²
2 nd layer:	Binder Plex 1510:	0,9 kg/m ²
	Filler for selfleveling Plex filler:	1.8 kg/m ²
	Pigment	0,02 kg/m ²
	Flakes	0,5 kg/m ²
3 rd layer:	Topcoat Plex 1690:	0,3 kg/m ²
	2 nd layer: Topcoat Plex 1690	0,3 kg/m ²

PROPERTIES:

D SHORE Hardness

D 80

Compressive strength

65 MPa

Bond strength

>1.5 MPa

Temperature resistance

Up to 80°C at 4 mm

Slip resistance

adjustable R9 - R13

